震击器实验台

DZZR-C Jar tester

Description 描述		Technical Specification 技术参数		Qty	Unit
Max PUSH		1,300KN/292,500LBS 最大推力 1300KN/132T			
Max PULL		1,100KN/247,500LBS 最大拉力 1100KN/112T			
stroke		40in. 行程 40 英寸			
Max Tool Diameter		13in. 最大工具直径			
Max Tool Capacit		45ft 最大工具长度			
Hydraulic power system 液压动力系统		Motor: power is 7.5KW, speed is 1460rpm, required voltage is 380V / 50HZ 电机 7.5KW，转速 1460r/min，电压 380V，频率 50HZ		1	Set 套
		Hydraulic pump type-Variable piston pump 液压泵类型：变量柱塞泵			
		MAX. pressure: 45667PSi 最大工作压力：31.5 兆帕			
		Oil level reminder function 具备缺油（声光）报警功能			
		Oil tankcapacity 60 Gal/160 L 油箱容积:230L			
Make up/ break out main engine 主机	Sensor 传感器	Pressure range 0-5800PSi 适用压力范围 0-40MPa		2	Set 套
		Working voltage DC24V 工作电压 DC24V			
		Accuracy ±0.2% 精准度±0.2%			
	Frame 机架	Material:Manganese steel 材质：锰钢		1	Set 套
		Structure 结构	Hydraulic cylinder end connectio 油缸端连接		
			Tail end connection (can be easily moved, fixed by inserting a pin) 尾端连接（可轻松移动，插入销轴固定）		
			1.2 sets of sliding support rollers 滑移支撑滚轮 2 2.Rollers at four corners 四角有滚轮 3.Replace the slot according to the diameter 根据直径更换卡槽位置		
			It is recommended to fix the rack with anchor bolts 建议机架用地脚螺栓固定		
		MAX. axial force 675,000 LBS 最大轴向受力 3,000KN			
		Frame size/Length×width× height 44.3′×45″×19″ 尺寸 13500×1150×483mm			
液压油缸		QTY 1 , stroke 40″ 数量 1 个，行程 1 M		1	Set 套
		Flange connection 法兰连接			

<table>
<tr><td rowspan="15">控制台
Console</td><td colspan="2">Hydraulic operation console dimension: 1410*900*1135mm
液压操作台尺寸: 1410*900*1135mm</td></tr>
<tr><td colspan="2">The hydraulic power system is placed under the control console 液压动力系统放在操作台下方</td></tr>
<tr><td colspan="2">English interface 英文界面</td></tr>
<tr><td colspan="2">Industrial Computer 工控机（工业用计算机）</td></tr>
<tr><td colspan="2">15” touch screen monitor, keyboard, mouse, stand 触摸屏 15”显示器，键盘、鼠标、支架</td></tr>
<tr><td rowspan="3">One working interface 工作界面 1 个</td><td>Operator and report name can be entered 可输入操作者和报告名称</td></tr>
<tr><td>Tool type and models can be selected in the drop-down list
可在下拉表中调取工具类型、规格</td></tr>
<tr><td>The system displays time, push and pull force and curve in real time
系统实时显示时间、推拉力和曲线</td></tr>
<tr><td rowspan="2">PDF Report
报告 PDF</td><td>Automatically generate PDF report (record push and pull force and curve)
自动生成 PDF 报告（记录推拉力及曲线）</td></tr>
<tr><td>The PDF report automatically generates a serial number and is saved in the root directory of disk D. The name can be modified.
PDF 报告自动生成序列号并保存在 D 盘根目录，可修改名称</td></tr>
<tr><td colspan="2">USB port, can copy the report USB 接口，可将报告拷贝</td></tr>
<tr><td colspan="2">Safe and transparent shield,UL bulletproof level 1 安全可视防护罩，UL 防弹一级</td></tr>
<tr><td colspan="2">1 Control lever 手动操作杆 1 个</td></tr>
<tr><td colspan="2">Scram button 急停按钮</td></tr>
<tr><td colspan="2">Noise level < 80 dB (A) 控制台噪音等级 80 dB (A)</td></tr>
<tr><td colspan="2">Pressure regulating valve 1 压力调节阀 1 个</td></tr>
<tr><td>Cylinder seal
油缸密封</td><td>The standard
标配</td><td>Taiwan 台湾</td></tr>
<tr><td>Connection seal
连接密封</td><td>The standard
标配</td><td>Taper sealing 锥度密封</td></tr>
<tr><td>Test connector 测试接头</td><td>The standard
标配</td><td>NC38 / NC50 / 6-5/8REG PIN and BOX
6 EA 共计 6 个</td></tr>
<tr><td>Hydraulic oil pipe
液压油管</td><td>The standard
标配</td><td>Qingdao, China 青岛第六橡胶厂</td></tr>
<tr><td>Printer
打印机</td><td>The standard
标配</td><td>Laser printer, made in China 激光，中国制造</td></tr>
<tr><td>physical dimension
设备外形参数</td><td colspan="2">Frame size/Length×width× height ： 49.4’×45″×19″
外观尺寸 15060×1150×483mm</td></tr>
<tr><td>设备总重量</td><td colspan="2">4,900kg 4.9T</td></tr>
<tr><td>Customer to provide
客户自备</td><td colspan="2">Anti-wear hydraulic oil 160L
抗磨液压油 160 公升</td></tr>
</table>

附 1：随机备件清单 Parts List

NO.	名称 ITEMS	数量 QTY
1	油缸密封 seal	2 套/Set
2	液压油滤芯 Filter Elements	4 个/EA

附 2、质量保证及交货期

Quality assurance and delivery time

1、质量保证 Quality assurance

1.1 我们有丰富的制造经验，有 157 个国内外用户，设备非常稳定

We have rich manufacturing experience, 157 domestic and foreign users, and the equipment is very stable

1.2 质量保证期为合格交货之日起 12 个月

The quality assurance period is 12 months from the date of qualified delivery

1.3 质保期间，设备如果出现问题，我们承诺 2 日内提供解决方案。

During the warranty period, if there is any problem with the equipment, We promise to provide a solution within 2 days.

2、交货期：合同生效后 30 天内。

Delivery time: within 30 days after the contract takes effect

附 3、随机文件 Random document

1、产品合格证；2、出厂试验报告；3、设备装车清单

4、备件清单；5、产品使用说明书（含计算机操作说明书）

1. Product certificate; 2. Factory test report;

3. Main accessories certificate 4. Parts List

5. Product instruction manual (including computer operation manual)